



# PV Power Analyzer

Type VK-PA-1000

**I-V Tracing and Maximum Power Point Tracking for solar cell modules up to 100 V & 1 A**  
**Comes with state-of-the-art control software**



## Specifications



Measurement Range	Voltage: 100 V – 500 mV (8 Ranges) Current: 1 A – 50 uA (15 Ranges)			
Minimum Resolution (Max. 6½-digits)	Set		Measure	
	27 μV	1.5 nA	62 nV	12 pA
Measuring Technique	Electronic Load Type			
Inputs	Front: 4 probes for PV devise			
A/D Converters	24 Bit (2 independent ADCs for V & I measurements)			
User Interface and data collecting	Computer software is provided for control of all the functions and data logging. Measurement data can be saved as a text file (.csv or .txt) and directly plotted on Microsoft Excel graph. (Windows based PC required)			
Communication	Bluetooth			
Power Requirement	100 VAC (50-60 Hz) 230 VAC (50-60 Hz)			
Electrical standard				
Dimensions, Weight	260 mm(W) x 350 mm(D) x 133 mm(H), 5 kg			

## Features of Solar Cell I-V Tracer

User selectable START, END and STEP voltages. Plots current and power vs. voltage curves. Calculated results include  $V_{oc}$ ,  $I_{sc}$ ,  $J_{sc}$ ,  $P_{max}$ ,  $V_{mpp}$ ,  $I_{mpp}$ , FF,  $R_s$ ,  $R_{sh}$ ,  $\eta_{activeA}$ , and  $\eta_{geoA}$ . User can set the desired scan speed, scan time, or holding time. Advanced I-V option allows initial, middle, and end point holding times. I vs. t transient plot for all data points and/or under a selected fixed voltage. "Programmed continuous I-V" function allows user to take series of IV curves on given time intervals. Dedicated I-V curve fitting function included to the control software.

## Features of Maximum Power Point Tracking (MPPT) Function

Analyzer acts like the best load for the cell to extract maximum power point (MPP) and keep tracking MPP continuously. Plots  $P_{max}$ ,  $V_{mpp}$ ,  $I_{mpp}$  and Efficiency vs. time curves and also display current/power vs. voltage plots.



## SPD Laboratory, Inc.

2-35-1 Johoku, Hamamatsu, 432-8011, JAPAN  
 Tel: +81-53-474-7901 Fax: +81-53-401-7080

Email: [ing@spd-lab.com](mailto:ing@spd-lab.com)

Web: <http://www.spdlab.com/English/VK-PA-1000.html>